

Capitex Road Bonding Filler adhesive

DESCRIPTION

Capitex Road Bonding Filler adhesive is a quality product from capitex and product is specially designed for Indian roads. **Capitex Road Bonding Filler adhesive** in the form of microscopic particles dispersed with aggregates, which acts as suspending medium during patch repairs.

Capitex Road Bonding Filler adhesive are low viscous enough to be applied at different atmospheric temperatures without heating. It's property affect by changes of temperature like hot applied bitumen; they become hard immediately after fixing.

It is necessary for Capitex Road Bonding Filler adhesive to remain viscous long enough to be spread, it is desirable that the traffic should be kept off the work for 15 Mins after rolling or at least until it is clear that the compound aggregates dried .If it is not possible to close the traffic, then a temporary speed limit of 10-20 km per hour is allowed until the surface dries completely.

ADVANTAGES

1. Cold applied material hence heating process is avoided.
2. Require no bitumen Boilers or Special Plant: The cost of field operation in road works is considerably reduced because all that necessary is the pouring cans or spray pumps. For small works or Patch repairs even a Mixer is not requiring, because it is completely readily mixed aggregates ready to use. Easy to apply as it does not require any heating or special boiler or pavers. Hence anyone can do application part easily.
3. **Capitex Road Bonding Filler adhesive** can be used over wet surface and work can be carried out during the monsoon period as long as the rain is not heavy enough to wash away the film of **Capitex Road Bonding Filler adhesive**.
4. **Capitex Road Bonding Filler adhesive** is non-toxic and will not harm the fish or plant life.

METHOD OF APPLICATION

The surface or pothole to be repaired must be swept clean of all dust & loose material by air compressor. If dust is more & cannot be cleaned, then it requires a little primer (Bitumen Base) should be brushed over the area to be patched.

Pothole should be cut in square and rectangle shape with mechanical cutter or by chisel & hammer.

Capitex Road Bonding Filler adhesive (Cold Mix adhesive) should then spread evenly with rakes, Forks, or Shovels to the desired thickness & contour allowing for consolidation. After the cold mix has been compacted with the help of wooden or stone rammer. It should be opened to traffic after 15 Minutes or when the cold mix has definitely set hard.

SPECIFIC USES

- (A) Road resurfacing
- (B) Repairs to pot holes/patch
- (C) Surface dressing
- (D) In level crossing of rails, platforms etc.
- (E) Premix carpeting
- (F) Runway repair.
- (G) Cold paving

PACKING

50 KG HDPE Bags

QUALITY ASSURANCE

AS PER ISO 9001